

1. GENERAL CHARACTERISTICS



- Cupboards made of cold-rolled sheet, with weld wire continue of copper of 0,8 - 1,0 mm and for points to obtain an inflexibility and ideal stability.
- Structure endowed by means of 4 wheels that allow an easy mobility of the cupboard
- Depth of 550 mm.
- Width of 1020
- Structures monoblock
- Possibility of front doors of blind
- Folding Key

1.1. Ended

Painting Finishes can be textured or smoothly

1.2. Structure

The cupboard is made by cold-rolled sheet of steel, of a thickness between 0,8 mm and 1,2 mm (depending on the part of the cupboard) by the reference faith - P01 equivalent to the European norm EN-10130, by a resistance of 38 kg to the mm. This one sheet is considered to be most adapted for the manufacture of this type of products, in view of his low content in carbon, which certain elasticity allows for conformations in right angle without never coming to the point of break, offering in turn a great conductivity for his union by means of weld for resistance.

1.3. Equipment of series

- 11 fixed Shelves for horizontal storage
- Specific housing for loaders
- System of wheels with front brakes
- Closing with 3 points of anchorage
- Game of drawers and lateral handles
- Perforations doors for major ventilation.
- Doors with interior reinforcement
- Singings rounded to reduce risks of impact
- 6/7 Schuko base captures
- Electrical Connection of 2.5m
- Differential Protection
- Magneto 16 To

1.4. Capacities

NUMBER OF LEVELS	12 = (11baldas + Nivel inf.)		
	Reference	ELBF1050	ELPF1050
COMPUTERS 10"		35(33+2inf.)	35(33+2inf.)
COMPUTERS 12"		35(33+2inf.)	24 (2 x nivel)
COMPUTERS 13,3"		24(2xnivel)	24 (2 x nivel)
COMPUTERS 14"		24(2xnivel)	24 (2 x nivel)

1.5. Wheels

The wheels allow us to displace easily and comfortably the cupboard if need to load weight.

These wheels are composed by a brake that allows the power to fix the cupboard, once placed in the space.

2. PAINTING

Superficial treatment of the cupboard before the process of application of the painting powder epoxi-polyester.

Painting: Covering in powder formulated with a mixture of resins epoxi-polyester with good mechanical and chemical properties.

*The spots of pen and permanent felt-tip pen will have to be cleaned immediately.

Colores / Couleurs / Colours

Cuerpo / Corps / Structure



Persiana / Rideau / Shutter





EC -SYSTEM GAPSA

Raw material

Respectful suppliers with the environment in this manufacturing processes

Preference to recycled materials and painting without solvents

Maximum reduction of the mechanization residue

Productive process

Minimization of the resources consumption

Control of atmospheric emissions and spillages

Treatment of waster by means of installation filter system

Segregation of all generated residues

Identification of pieces by means of recyclability triangle

Painting liquidates without solvents and ponder painting without nanomaterials



Logistics

Suppliers with certified systems of environmental management

Maximum optimization of the utilization of space

Planning of routes with ecological orientation

End of life

Easy dismantlement of the cupboard

Marked pieces to promote and facilitate its recycling

High degree of cupboards recyclability

Useful life

Product designed for an easy repair

Sale of the second hand (reutilization)

Products designed for a long life

Environmental Certifications



Raw material

Productive process

Logistics

End of life

Useful life