

Card of Product

# Roller



## 1. GENERAL CHARACTERISTICS



- **Cupboards made of cold-rolled sheet, with weld wire continue of copper of 0,7 - 0,8 mm** and for points to obtain an inflexibility and ideal stability.
- **Structure endowed by means of 4 wheels** that allow an easy mobility of the cupboard
- **Depth of 450 mm.**
- **Width 1200, 1020, 800, and 600 mm** according to model.
- **Shelves endowed with guides for hanging folders.** Exempting cupboards of 700, hillocks and clothiers the rest of models the top this one endowed with guides for hanging folders.
- **Blind of 30 mm** of width , available in the whole range of colors of the color chart GAPSA.
- Structures monoblock.
- **Folding Key.**

### 1.1. Ended

Painting Finishes can be textured or smoothly

### 1.2. Structure

**The cupboard is made by cold-rolled sheet of steel, of a thickness between 0,8 mm and 1,2 mm** (depending on the part of the cupboard) by the reference faith - P01 equivalent to the European norm EN-10130, by a resistance of 38 kg to the mm. This one sheet is considered to be most adapted for the manufacture of this type of products, in view of his low content in carbon, which certain elasticity allows for conformations in right angle without never coming to the point of break, offering in turn a great conductivity for his union by means of weld for resistance.

### 1.3. Interior wings



- Interior panels of the cupboard, composed by sheet of cold-rolled band of low steel in quality carbon DC01, being the thickness of the same one of 0,8mm.
- Subordination of the interior panels of the cupboard both for the bottom and for the top.
- **Regulation of the shelf every 25mm**


## 1.5. Wheels

One of the principal advantages more competitive of this cupboard is the use of his wheels, which they allow us to displace easily and comfortably the cupboard if need to load weight.

These wheels are composed by a brake that allows the power to fix the cupboard, once placed in the space

## 1.5. Closing

Closing that allows to obtain a highly ideal anticorrosion. Made of cold-rolled steel of 0,8mm of thickness. His system of assembly contributes a behavior of component of the blind on having been joined. The closing is composed by locks of 90 ° by possibility of up to 600 combinations and main key.



Drawer with ergonomic design to facilitate the opening and closing of the cupboard.

## 2. PAINTING


Superficial treatment of the cupboard before the process of application of the painting powder epoxi-polyester.

Painting: Covering in powder formulated with a mixture of resins epoxi-polyester with good mechanical and chemical properties.

\*The spots of pen and permanent felt-tip pen will have to be cleaned immediately.

## Colores / Couleurs / Colours

### Cuerpo / Corps / Structure



### Persiana / Rideau / Shutter





## EC -SYSTEM GAPSA

### Raw material

Respectful suppliers with the environment in this manufacturing processes

Preference to recycled materials and painting without solvents

Maximum reduction of the mechanization residue

### Productive process

Minimization of the resources consumption

Control of atmospheric emissions and spillages

Treatment of waster by means of installation filter system

Segregation of all generated residues

Identification of pieces by means of recyclability triangle

Painting liquidates without solvents and ponder painting without nanomaterials



## Logistics

Suppliers with certified systems of environmental management

Maximum optimization of the utilization of space

Planning of routes with ecological orientation

## End of life

Easy dismantlement of the cupboard

Marked pieces to promote and facilitate its recycling

High degree of cupboards recyclability

## Useful life

Product designed for an easy repair

Sale of the second hand (reutilization)

Products designed for a long life

## Environmenta



NG-PP

# Raw material

# Productive process

# Logystics

# End of life

Useful life